

## **DECLARATION OF PERFORMANCE**

We hereby declare that the product range identified as,

## LPL, 40-225mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as a Symmetrical Wall Tie.



Declaration Number:	L0109-02-CA
Intended Use:	Wall tie for connecting two new leaves of stone
Approved Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Approved Body Number:	1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above approved body.

Essential Characteristics		
Compressive Load Capacity (cavity +15mm):	1140N	
Tensile Load Capacity:	8690N	
Capacities given for:		
Overall Wall Tie Length:	40mm-225mm	
Design Cavity Width:	Not relevant	
Minimum Embedment Depth:	Not relevant	
Minimum Cover to Face of Wall:	Not relevant	
Minimum Mortar Joint Thickness:	Not relevant	
Minimum Mortar Class:	Not relevant	
Displacement at 1/3 Load Capacity		





## **DECLARATION OF PERFORMANCE**

In Compression:	0.24	
In Tension:	1.01	
Failure Modes:		
In Compression:	Bending of tie	
In Tension:	Bending of tie at 'L' End	
Water Shedding Capacity:	Not relevant	
Recommended Spacing:	As required	
Durability		
Material Coating Reference:	3	
Steel Grade:	1.4301/1.4401	
Dangerous Substance	None	

Signed for and on behalf of the manufacturer by

Rune Magnusson

Regional Managing Director, UK & Asia

26th March 2025

Manufactured by;

**Leviat Limited**President Way

President Park

Sheffield, S4 7UR

United Kingdom



