

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

MP21, 125-225mm

conforms to the provisions of, ZA Annex, EN 845-1:2013+A1:2016 as a Asymmetrical Wall Tie.

ϵ

Declaration Number:	L0100-00-CE
Intended Use:	Wall tie for use with the Ancon 21/18 Omega channel system to connect a new stone leaf to an existing structure
Notified Body:	Technical and Test Institute for Constructions Prague, Branch 0600 - Brno, Hněvkovského 77, 617 00 Brno - Komárov, Czech Republic
Notified Body Number:	1020

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics		
Compressive Load Capacity (cavity +15mm):	840N	
Tensile Load Capacity:	5490N	
Capacities given for:		
Overall Wall Tie Length:	125mm-225mm	
Design Cavity Width:	Not relevant	
Minimum Embedment Depth:	Not relevant	
Minimum Cover to Face of Wall:	Not relevant	
Minimum Mortar Joint Thickness:	Not relevant	
Minimum Mortar Class:	Not relevant	
Displacement at 1/3 Load Capacity		





DECLARATION OF PERFORMANCE

In Compression:	0.18	
In Tension:	0.63	
Failure Modes:		
In Compression:	Bending of tie	
In Tension:	Pull-out of tie	
Water Shedding Capacity:	Not relevant	
Recommended Spacing:	As required	
Durability		
Material Coating Reference:	3	
Steel Grade:	1.4301/1.4401	
Dangerous Substance	None	

Signed for and on behalf of the manufacturer by

Rune Magnusson

Managing Director Europe West & APAC

16th September 2024

Manufactured by;

Leviat Limited

President Way President Park

Sheffield, S4 7UR United Kingdom

A CRH COMPANY