

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

MPB, 125-225mm

conforms to the provisions of, ZA Annex, EN 845-1:2013+A1:2016 as a Asymmetrical Wall Tie.

CE

| Declaration Number: L0102-00-CE |
|---------------------------------|
|---------------------------------|

| Intended Use: | Frame cramp for connecting a new stone leaf to an existing structure |
|-----------------------|--|
| Notified Body: | Technical and Test Institute for Constructions Prague, Branch 0600 - Brno, Hněvkovského 77, 617 00 Brno - Komárov, Czech Republic |
| Notified Body Number: | 1020 |

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

| Essential Characteristics | | |
|---|--------------|--|
| Compressive Load Capacity (cavity +15mm): | 1150N | |
| Tensile Load Capacity: | 3460N | |
| Capacities given for: | | |
| Overall Wall Tie Length: | 125mm-225mm | |
| Design Cavity Width: | Not relevant | |
| Minimum Embedment Depth: | Not relevant | |
| Minimum Cover to Face of Wall: | Not relevant | |
| Minimum Mortar Joint Thickness: | Not relevant | |
| Minimum Mortar Class: | Not relevant | |
| Displacement at 1/3 Load Capacity | | |



Leviat.com



DECLARATION OF PERFORMANCE

| In Compression: | 0.24 | |
|-----------------------------|------------------------|--|
| In Tension: | 0.7 | |
| Failure Modes: | | |
| In Compression: | Bending of tie | |
| In Tension: | Bending of upstand leg | |
| Water Shedding Capacity: | Not relevant | |
| Recommended Spacing: | As required | |
| Durability | | |
| Material Coating Reference: | 3 | |
| Steel Grade: | 1.4301/1.4401 | |
| Dangerous Substance | None | |

Signed for and on behalf of the manufacturer by

Rune Magnusson Managing Director Europe West & APAC 16th September 2024

Manufactured by;

Leviat Limited President Way President Park Sheffield, S4 7UR United Kingdom

