

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

SD30, 300mm

conforms to the provisions of, ZA Annex, EN 845-1:2013+A1:2016 as an Asymmetrical Wall Tie.



| | |
|----------------------------|--------------------|
| Declaration Number: | L0077-00-CE |
|----------------------------|--------------------|

| | |
|-----------------------|---|
| Intended Use: | Wall tie for use with the Ancon 30/20 channel system to connect a new masonry leaf to an existing structure. Suitable for 220-245mm cavities. |
| Notified Body: | Technical and Test Institute for Constructions Prague, Branch 0600 - Brno, Hněvkovského 77, 617 00 Brno - Komárov, Czech Republic |
| Notified Body Number: | 1020 |

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

| Essential Characteristics | |
|--|------------------|
| Compressive Load Capacity (cavity +15mm): | 760N |
| Compressive Load Capacity (design cavity): | 1360N |
| Tensile Load Capacity: | 3610N |
| Capacities given for: | |
| Overall Wall Tie Length: | 300mm |
| Design Cavity Width: | 220-245mm |
| Minimum Embedment Depth: | 50mm |
| Minimum Cover to Face of Wall: | 20mm |
| Minimum Mortar Joint Thickness: | 10mm |
| Minimum Mortar Class: | Type M2 |

DECLARATION OF PERFORMANCE

| | |
|--|------------------------|
| Displacement at 1/3 Load Capacity | |
| In Compression: | 0.22 |
| In Tension: | 0.19 |
| Failure Modes: | |
| In Compression: | Bending of tie |
| In Tension: | Pull-out of tie |
| Water Shedding Capacity: | Resistant |
| Recommended Spacing: | As required |
| Durability | |
| Material Coating Reference: | 3 |
| Steel Grade: | 1.4301/1.4401 |
| Dangerous Substance | None |

Signed for and on behalf of the manufacturer by



 Rune Magnusson
 Managing Director Europe West & APAC
 16th September 2024

Manufactured by:

Leviat Limited
 President Way
 President Park
 Sheffield, S4 7UR
 United Kingdom