

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

Ancon Staifix HRD4 250mm

conforms to the provisions of, ZA Annex, EN 845-1:2013+A1:2016 as a Symmetrical Wall Tie.



Declaration Number:	L0133-00-CE
Intended Use:	Type 4 wall tie for connecting two leaves of a cavity wall.
Notified Body:	Technical and Test Institute for Constructions Prague, Branch 0600 - Brno, Hněvkovského 77, 617 00 Brno - Komárov, Czech Republic
Notified Body Number:	1020

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics		
Compressive Load Capacity (cavity +15mm):	350N	
Tensile Load Capacity (at min embedment):	650N	
Capacities given for:		
Overall Wall Tie Length:	250mm	
Design Cavity Width:	101-125mm	
Minimum Embedment Depth:	50mm	
Minimum Cover to Face of Wall:	20mm	
Minimum Mortar Joint Thickness:	10mm	
Minimum Mortar Class:	Type M2	
Displacement at 1/3 Load Capacity		





DECLARATION OF PERFORMANCE

In Compression:	0.13	
In Tension:	0.66	
Failure Modes:		
In Compression:	Bending of tie	
In Tension:	Straightening of tie	
Water Shedding Capacity:	Resistant	
Recommended Spacing:	Refer to PD 6697	
Durability		
Material Coating Reference:	3/23	
Steel Grade:	1.4301/1.4401/1.4597	
Dangerous Substance	None	

Signed for and on behalf of the manufacturer by

Rune Magnusson

Managing Director, UK & Asia

28th October 2024

Manufactured by;

Leviat Limited

President Way President Park

Sheffield, S4 7UR United Kingdom

A CRH COMPANY