

## **DECLARATION OF PERFORMANCE**

We hereby declare that the product range identified as,

## CCB-JJ 210-260mm

conforms to the provisions of, ZA Annex, EN 845-1:2013+A1:2016 as a Symmetrical Wall Tie.



| Declaration Number:   | L0145-00-CE   |
|-----------------------|---|
|                       |   |
| Intended Use:         | Type 2 wall tie for connecting two leaves of cellular clay thin-<br>joint blockwork. Suitable for 50-100mm cavities.              |
| Notified Body:        | Technical and Test Institute for Constructions Prague, Branch 0600 - Brno, Hněvkovského 77, 617 00 Brno - Komárov, Czech Republic |
| Notified Body Number: | 1020  |

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

| Essential Characteristics                 |                           |  |
|---|---------------------------|--|
| Compressive Load Capacity (cavity +15mm): | 1050N                     |  |
| Tensile Load Capacity:                    | 1800N                     |  |
| Capacities given for:                     |                           |  |
| Overall Wall Tie Length:                  | 210mm-260mm               |  |
| Design Cavity Width:                      | 50mm-100mm                |  |
| Minimum Embedment Depth:                  | Cellular Clay Block 80mm  |  |
| Minimum Cover to Face of Wall:            | 20mm                      |  |
| Minimum Mortar Joint Thickness:           | 1mm                       |  |
| Minimum Mortar Class:                     | Wienerberger Zero Plus/M2 |  |
| Displacement at 1/3 Load Capacity         |                           |  |





## **DECLARATION OF PERFORMANCE**

| In Compression:             | 0.10             |  |
|-----------------------------|------------------|--|
| In Tension:                 | 0.15             |  |
| Failure Modes:              |                  |  |
| In Compression:             | Bending of tie   |  |
| In Tension:                 | Pull-out of tie  |  |
| Water Shedding Capacity:    | Resistant        |  |
| Recommended Spacing:        | Refer to PD 6697 |  |
| Durability                  |                  |  |
| Material Coating Reference: | 3                |  |
| Steel Grade:                | 1.4301/1.4401    |  |
| Dangerous Substance         | None             |  |

Signed for and on behalf of the manufacturer by

Rune Magnusson

Managing Director, UK & Asia

28th October 2024

Manufactured by;

**Leviat Limited** 

President Way President Park

Sheffield, S4 7UR

United Kingdom

